



The Galvanised Cycle Stand

The Galvanised Cycle Stand is manufactured from a 60mm diameter galvanised steel tube and designed to conform to cycle stand regulations on London's transport network. Supplied with orange reflective tape as standard (other colours are available upon request), tapping rails and signage plates can be added as required for easy identification by visually impaired pedestrians. The design of the Galvanised Cycle Stand allows cyclists to secure both the frame and wheel of the bicycle using their own security lock. Each stand is suitable for securing two bicycles.

The Galvanised Cycle Stand is available in galvanised and coated, and stainless steel finishes. RAL/BS numbers must be specified at time of order. Supplied ragged as standard; flanged versions are also available. Tapping rails and signage plates are fixed at 100mm and 300mm above the ground respectively. Signage plates incorporate the Cycle Parking 'P' and cycle symbol signs as standard ensuring the parking area is easily identifiable at all times.

Product Range

Order Code	Description	Weight
138 515 290	Ragged (galvanised)*	11.5kg
138 515 295	Flanged (galvanised)*	9.5kg
138 515 290T	Ragged with Tapping Rail (galvanised)*	14.5kg
138 515 295T	Flanged with Tapping Rail (galvanised)*	12.5kg
138 515 300	Ragged with Signage Plate (galvanised)*	15.5kg
138 515 305	Flanged with Signage Plate (galvanised)*	13.5kg
138 515 300T	Ragged with Tapping Rail and Signage Plate (galvanised)*	18.5kg
138 515 305T	Flanged with Tapping Rail and Signage Plate (galvanised)*	16.5kg

**Versions can be colour coated upon request (please specify BS/RAL numbers)*

Installation Parts

138 100 994	12mm Expanding Bolt (flanged only; 6 required per stand)
-------------	--

Product details

750mm x 800mm (height x length).

60mm diameter tube.

3mm wall thickness.

Signage Plate: 150mm x 680mm (height x length).

300mm below ground (ragged only).

Installation & use

Flanged versions require bolting to established concrete of at least 300mm³ per leg.
Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 350mm (length x width x depth).

Allow at least 800mm between stands and a minimum of 450mm from any obstruction.

This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk

Procter Contracts - North
Isabella Road
Leeds
LS25 2DY

Procter Contracts - South West
11 Pantglas Industrial Estate
Bedwas
CF83 8XD

Procter Contracts -South East
Codham Hall
Brentwood
CM13 3JT



The Galvanised Cycle Stand

The Galvanised Cycle Stand is designed to conform to the Greater Manchester transport cycle stand regulations. At 1000mm wide it provides ample storage for securing larger styles of bicycle. The design of the Manchester Cycle Stand allows cyclists to secure both the frame and wheel of the bicycle using their own security lock. Each stand is suitable for securing two bicycles.

Manufactured from galvanised mild steel, these stands are available in galvanised and coated, and stainless steel finishes. RAL/BS numbers must be specified at time of order. Supplied ragged as standard; flanged versions are also available.

Supplied with orange reflective tape as standard (other colours are available upon request). Tapping rails and signage plates can be added as required; fixed at 100mm and 300mm above the ground respectively. Signage plates incorporate the Cycle Parking 'P' and cycle symbol signs as standard ensuring the parking area is easily identifiable at all times.

Product Range

Order Code	Description	Weight
138 515 310	Ragged (galvanised)*	12.3kg
138 515 315	Flanged (galvanised)*	10.4kg
138 515 310T	Ragged with Tapping Rail (galvanised)*	16.3kg
138 515 315T	Flanged with Tapping Rail (galvanised)*	14.4kg
138 515 320	Ragged with Signage Plate (galvanised)*	17.5kg
138 515 325	Flanged with Signage Plate (galvanised)*	15.6kg
138 515 320T	Ragged with Tapping Rail and Signage Plate (galvanised)*	21.5kg
138 515 325T	Flanged with Tapping Rail and Signage Plate (galvanised)*	19.6kg

**Versions can be colour coated upon request (please specify BS/RAL numbers)*

Installation Parts

138 100 994 12mm Expanding Bolt (flanged only; 6 required per stand)

Product details

750mm x 1000mm (height x length).

60mm diameter tube.

3mm wall thickness.

Signage Plate: 150mm x 880mm (height x length).

300mm below ground (ragged only).

Installation & use

Flanged versions require bolting to established concrete of at least 300mm³ per leg.

Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 350mm (length x width x depth).

Allow at least 800mm between stands and a minimum of 450mm from any obstruction.

~~This product is guaranteed for 12 months (if installed and used correctly).~~

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk